


# LEARNING ABOUT

In the world of pneumatics, which is considered mature, it is rare to encounter completely new and different products. ONE a compressed air treatment unit with a high degree of integration, that encompassed numerous pneumatic functions. In fact, it contains so many innovations that a single patent is not enough to safeguard it against imitation – three separate patent applications have been registered with a total of 39 claims. This unit is so innovative that it won the international novelty award at Fluidtrans Compomac. ONE has a single high-performance valve on the main flow that handles all the functions from regulation to relief. It is controlled by a high-precision pilot regulator with controlled relief, in series with the manual on-off valve, the electric valve and the progressive actuator. Unification of the valve has led to a significant reduction in overall dimensions, enhanced capacity, precision and response speed.



## INTEGRATION

One single unit houses the threaded ports, filter, condensate drain, pressure regulator, shut-off valve, soft start valve, pressure switch and three supplementary air intakes.



## MINIATURISATION



Extremely reduced dimensions, considering the extra-high performance and flow rate reachable.




No clearance is required above and below it to make adjustments or change the filter or other components. The actual space occupied is thus further reduced.



It weighs slightly more than one kilo instead of the 8.8 to 17.6 pounds of conventional units.

## EASY ADJUSTMENTS AND LITTLE MAINTENANCE

The entire user interface is at the front, which means that everything is visible and easy to reach. All the adjustments are made using the push-lock knobs (no need for wrenches or screwdrivers), thus preventing accidental operations or manoeuvres.



## CONFIGURABILITY

Considering that ONE is reduced in size but highly performing, and it can integrate tenths of functions, a single unit can cover the entire range of applications, with cut-clear advantages in terms of standardisation and reduction of the number of codes handled and goods in stock. With a single size there are thousands of different configurations. For example, there is choice between 1/4", 3/8", 1/2", 3/4" or 1" threaded ports, manual and/or electric on-off or progressive valves, etc. The customer decides the configuration he wants and creates the code, using the key-to-coding table shown below in this catalogue. He will receive the unit he wants marked with its code and the correct pneumatic diagram.

## WHAT YOU CAN SEE FROM THE OUTSIDE


- ① Air intake, with swivel threaded port
- ② Fixing hole
- ③ Access to filter cartridge
- ④ Pressure regulation
- ⑥ Manual override (shut-off valve electrical)
- ⑦ Soft start valve regulation
- ⑧ Switching pressure regulation
- ⑨ Air outlet, with swivel threaded port
- ⑩ LED signalling unit ON
- ⑪ LED signalling pressure below the value set on pressure switch
- ⑫ LED signalling pressure over the value set on pressure switch
- ⑬ 5-pin M12x1 electrical connector
- ⑭ Pressure gauge
- ⑮ BSPP 1/4" air intake. Another regulated air intake and a filtered non-regulated air intake are situated on the top
- ⑯ Air exhaust with a BSPP 1/4" silencer
- ⑰ Condensate tank
- ⑱ Condensate drain
- ⑲ Clogged filter signal



THREADED PORTS




- The threaded ports at the air intake and outlet are the swivel type to facilitate coupling with the supply and delivery pipes. In this way, the unit can be mounted or removed without dismantling the pipes.
- A range of 5 different threads, 1/4", 3/8", 1/2", 3/4" and 1" is also available.
- The thread for the supply pipe may differ from that of the delivery one.



- If the filter gets so clogged up that it causes an excessive drop in pressure as the air passes through, the optical filter blockage indicator will project (see detail A) to indicate that the filter cartridge must be replaced.
- The cartridge can be replaced by unscrewing a plug at the front. This system is functional and, unlike conventional filters, does not require manoeuvring space below the unit.
- An automatic stop on-off valve is incorporated in the unit: when the filter plug is unscrewed, the valve closes automatically. This means there is not need to a tap upstream and there is no risk of the plug being ejected violently.

CONDENSATE DRAIN



- The condensate drain is located downstream of the filter and thus uses cleaner air. This prevents the known problem of air leaks due to the deposit of dirt on the condensate discharge valve.
- You can request ONE with two types of condensate drain:
  - semi-automatic, type RMSA
  - automatic, of the floating type RA

SINGLE AIR EXHAUST



The air in the circuit is relieved via one outlet situated below the unit and fitted with silencer. If you want to convey air relief to prevent the emission of polluted air into the atmosphere, you can replace the silencer and install a fitting. (a pipe with a diameter of at least 6 mm is recommended)  
 Next to the air outlet there is the condensate drain, which in the RA version conveys the draining by inserting the pipe having internal diameter 6 mm in the lower port.

### SUPPLEMENTARY PORTS



In addition to the main outlet, there are three supplementary air ports with a BSPP 1/4" thread.

- one for filtered non-regulated air (A) for use, for example, with a compressed air gun.
- two for filtered regulated air (B).

The unit comes complete with supplementary plugged ports for use with A7 fittings.

### PANEL MOUNTING



ONE can be mounted inside the guard of the machine leaving only the front visible. This is a considerable advantage in terms of functionality and aesthetics as the user interface is entirely at the front. Among the accessories to be ordered separately, there is the kit of brackets for panel mounting.


### ELECTRICAL CONNECTION



A standard five-pin M12x1 connector, with IP67 protection is used for the opening solenoid valve and the pressure switch.

One cable only is required, thus improving reliability and reducing wiring times.

### SOFT START VALVE



- 1 Regulation for: **ONE** does not change with flow rate!
- 2 Initial regulation of conventional unit
- 3 Low flow rate: activation too abrupt
- 4 High flow rate: activation too slow
- 5 Even higher flow rate: never cuts in!

The soft start valve is an absolutely innovative feature among the functions provided by ONE.

Soft start valve available from the trade are generally based on the principle of leaving the passage of a small amount of air until the downstream pressure reaches a set value, and then opening the passage fully. In this way, the rate at which the pressure increases depends on the flow rate of the utilities, which often feature a continuous flow rate, for example a blow, and thus the starter can hardly activate. The solution offered by One is such that the pressure increases gradually and it is independent of the flow rate of the utilities. Pressure increase can be regulated precisely via the knob at the front.

Another piece of news, among the several possible configurations you can have the soft start valve operated by the manual V3V

# SPECIFICATIONS


AIR PREP

ONE: SPECIFICATIONS


TECHNICAL DATA		NPT 1/4"	NPT 3/8"	NPT 1/2"	NPT 3/4"	NPT 1"
Flow rate at 6.3 bar (0.6 MPa; 91 psi) $\Delta P$ 0.5 bar (0.05 MPa; 7.25 psi)	Nl/min	2200	2900		3600	
	scfm	78	102		127	
Flow rate at 6.3 bar (0.6 MPa; 91 psi) $\Delta P$ 1 bar (0.1 MPa; 14.5 psi)	Nl/min	2400	3300		4000	
	scfm	85	116		141	
Flow rate on discharge at 6 bar (0.1 MPa; 14.5 psi)	Nl/min			1600		
	scfm			56		
1/4" port flow rate of non-regulated filtered air at 6.3 bar (0.6 MPa; 91 psi) $\Delta p$ 1 bar	Nl/min			1800		
	scfm			64		
* Flow rate of each supplementary 1/4" filtered and regulated air port at 6.3 bar (0.63 MPa; 91 psi) $\Delta P$ 1 bar (0.1 MPa; 14.5 psi)	Nl/min			2400		
	scfm			85		
Fluid		Compressed air				
Setting range	bar	0,5 to 2 (7 to 30 psi)	0,5 to 4 (7 to 60 psi)		0,5 to 8 (7 to 120 psi)	
Degree of filtration	$\mu m$	5 (yellow) or 20 (white)				
Operating temperature range	bar	10				
	MPa	1				
	psi	145				
Operating temperature range	$^{\circ}C$	-10 to 50				
	$^{\circ}F$	14 to 122				
Class of protection		IP 65 with connector				
Insulation class of the solenoid valve		F155				
Switching time		100% ED				
Electrical connector		M12 x 1.5-pin to CEI IEC 60947-5-2				
Solenoid valve power	W	3/0.3				
Solenoid valve voltage	V	24 VDC $\pm$ 10%				
Pressure interval settable on the pressure switch	bar	0.5 to 10				
Pressure switch hysteresis (not adjustable)	bar	bar 0.4 to 0.8 (see diagram)				
Maximum pressure switch current	A	0.5				
Maximum pressure switch voltage	V	3 to 30 AC/DC				
Pressure switch contacts		Normally open (NO) and normally closed (NC)				
Number of switching		5 x 10 <sup>6</sup>				
Weight	pounds	From 2.53 to 2.75 according to configurations				
Wall fixing (max. panel thickness 0.4 inch):		Front, with M5 x 75 screws or back, with M6 x 70 screws The screws are included in the supply				
Mounting position		Vertical				
Direction of flow		From left to right				
* Total flow rate from two supplementary outlets and the main one cannot exceed 141 scfm at 91 psi with $\Delta P$ 14.5 psi						
Compatibility with oils		Please refer to page 5-4 of the technical documentation				

## WIRING DIAGRAM


Version with solenoid valve and pressure switch




Version with pressure switch




Version with solenoid valve



### PRESSURE SWITCH WIRING DIAGRAM




### PRESSURE SWITCH HYSTERESIS CHART



### FLOW CHARTS


#### 1/4"

Pm = 8 bar - 0.8 MPa - 116 psi  
Preset pressure




#### 3/8"

Pm = 8 bar - 0.8 MPa - 116 psi  
Preset pressure



#### 1/2" - 3/4" - 1"


Pm = 8 bar - 0.8 MPa - 116 psi  
Preset pressure





## EXTERNAL DESIGN

You can get thousands of different configurations. The external design differs according on the versions chosen.



<p><b>CLOGGED FILTER SIGNAL</b> ①</p> <p>PRESENT</p> <p>NOT PRESENT</p>	<p><b>V3V MANUAL</b> ②</p> <p>STANDARD</p> <p>LOCKABLE</p> <p>NOT PRESENT</p>	<p><b>V3V ELECTRICAL</b></p> <p>PRESENT</p> <p>NOT PRESENT</p> <p>in some versions holes are present</p> <p>in other configurations the cover has no holes</p>	<p><b>SOFT START VALVE</b> ④</p> <p>PRESENT</p> <p>NOT PRESENT</p>
<p><b>CONDENSATE DRAIN</b> ⑤</p> <p>AUTOMATIC (RA)</p> <p>RMSA</p>	<p><b>PRESSURE SWITCH</b></p> <p>PRESENT</p> <p>NOT PRESENT</p> <p>in some versions holes are present</p> <p>in other configurations the cover has no holes</p>	<p><b>ONE NON-ELECTRICAL</b></p>	

# HOW TO ORDER

## ORDERING CODES

You can choose among numerous variants and options. The product code so personalised is made up by compiling the diagram below. The code so compiled must be specified on the order. A label showing the code and its pneumatic diagram is affixed onto the product.


	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>F</b>	<b>G</b>	<b>H</b>	<b>I</b>	<b>L</b>
	ONE electrical or ONE non-electrical	Air intake	Degree of filtration	Clogged filter signal	Condensate drain	Pressure regulation	Valves	Pressure switch	Air outlet	Miscellaneous, special version
<b>EXAMPLE</b>	<b>54</b>	<b>A</b>	<b>2</b>	<b>1</b>	<b>1</b>	<b>2</b>	<b>7</b>	<b>1</b>	<b>A</b>	<b>0 0</b>
53	ONE non-electric	A 1/4" NPT	2 20µm (790 microinch)	0 NO	0 RMSA	2 0,5 to 2 bar (7 to 30 psi)	0 None	0 NO	A 1/4" NPT	00 Standard
54	ONE electric*	B 3/8" NPT	5 5µm (2000 microinch)	1 YES	1 automatic (RA)	4 0,5 to 4 bar (7 to 60 psi)	1 V3V manual	1 YES	B 3/8" NPT	
		C 1/2" NPT				8 0,5 to 8 bar (7 to 120 psi)	2 V3V manual with padlock		C 1/2" NPT	
		D 3/4" NPT					3 V3V manual and soft start valve		D 3/4" NPT	
		E 1" NPT					4 V3V manual with padlock and soft start valve		E 1" NPT	
							5 V3V manual and V3V electric			
							6 V3V manual with padlock and V3V electric			
							7 V3V manual and APR electric			
							8 V3V manual with padlock and APR electric			
							9 only V3V electric			
							A only APR electric			

\* a pressure switch version and/or electric V3V and/or electric progressive actuator.

● NB: versions valid only for the electric ONE (code 54...)


- A ONE electric or non-electric**  
**ONE non-electric:** there is no component actuated electrically: select code 53. In this case, the unit comes without any M12x1 connector, LED, pressure switch, or electric V3V.  
**ONE electric:** there is at least one component actuated electrically, and thus the pressure switch and/or electric V3V (and/or the electrical soft start valve) select code 54. In this case, the unit comes with the M12x1 connector and 3 LEDs. Only the LEDs associated with the functions installed will be active.
- B Air intake**  
 There are 5 different threads: 1/4", 3/8", 1/2", 3/4" and 1".
- C Degree of filtration**  
 A cartridge with a degree of filtering of 5 µm (790 microinch) yellow or 20 µm (2000 microinch) white is available. This value is marked on the plug.
- D Clogged filter signal**  
 If the filter gets so clogged up that it causes an excessive drop in pressure as the air passes through, the orange indicator will project from the body by a few millimetres.
- E Condensate drain**  
**RMSA:** the condensate is drained out automatically only by relieving the air pull the knurled knob for having the same result.  
**Automatic (RA):** a floating system that automatically drains the condensate out whenever the level of water in the bowl reaches the set value.
- F Pressure regulation**  
 There are three possible regulation fields.  
 The value is marked on the regulation knob..
- G Valves**  
 There are 11 different combinations. The electric valves are clearly selectable only if the initial code is 54, i.e. ONE electric.
- 0 - No valves present
  - 1 - V3V manual: is a 3/2 valve that in a set position allows the air to flow and in the other it closes the passage and discharges the pressure downstream.
  - 2 - V3V manual with padlock: like the previous one, with the possibility of inserting a padlock (included in the supply with 2 keys) in the valve closed position.
  - 3 - V3V manual and soft start valve: when the manual V3V valve is operated, the pressure starts to increase slowly, with a fine adjustable ramp, and when it reaches about 30-40% of the set value, the valve opens completely and the pressure rises to the set value.
  - 4 - V3V manual with padlock and soft start valve: like the previous, with the padlock device on the manual V3V in "OFF" position.
  - 5 - V3V manual and V3V electric: two V3V in series are present, one is manual the other electrical. By operating both the valve the air flow is allowed. If one or two are switched OFF, the air downstream is relieved. The electrical one can also be operated manually by reefing pushed the "TEST" button
  - 6 - V3V manual with padlock and V3V electric: like the previous, with the padlock device in "OFF" position.
  - 7 - V3V manual and APR electric: One manual V3V and one soft start valve are present. When both are operated, the pressure starts to increase slowly, with a fine adjustable ramp, and when it reaches about 30-40% of the set value, the valve opens completely and the pressure rises to the set value.
  - 8 - V3V manual with padlock and APR electric: like the previous, with the padlock device on the manual V3V in "OFF" position.
  - 9 - V3V electric: It's present only the electrical V3V. The valve will open if it is powered on. When the power supply is switched off, the valve closes and air downstream is relieved. The valve can also be operated manually by keeping pushed the test button.
  - A - APR electric: It's present only the electric soft start valve. When it is powered ON, the pressure starts to increase slowly, with a fine adjustable ramp, and when it reaches about 30-40% of the set value, the valve opens completely and the pressure rises to the set value.
- H Pressure switch**  
 The pressure switch has a switching contact, which means you can have a normally-open signal or a normally-close signal. It is also connected to the NC and NO LEDs which come on if the actual pressure is less or greater than the set pressure, respectively. The LEDs only come on if an electric signal is connected to them.
- I Air outlet**  
 Five different threads are available: 1/4", 3/8", 1/2", 3/4" and 1". It is possible to choose a thread other than the one on the inlet port.
- L Free positions for special executions.**

## PANEL MOUNTING BRACKETS




Code	Description
9200702	Kit - panel mounting brackets NB: fixing screws included

## COVER DISASSEMBLY WRENCH



Code	Description
9170401	Cover disassembly wrench


## SECURITY KNOB



Code	Description
9200703	Security knob apr/pressure switch


**NOTE:** Pull outwards to remove the knob from the APR/pressure switch on the unit. Insert the security knob and regulate the APR/ pressure switch. Then press the handle firmly to lock it in position. If the APR/pressure switch needs to be reset, remove the security knob by forcing it laterally with a screwdriver.

## STRAIGHT CONNECTOR




Code	Description
W0970513001	5-PIN M12X1 straight connector

## STRAIGHT CONNECTOR WITH WIRE




Code	Description
W0970513002	5-PIN M12X1 straight connector with wire L = 197 inch

## 90° CONNECTOR




Code	Description
W0970513003	M12X1 5-PIN 90° connector

## 90° CONNECTOR WITH WIRE




Code	Description
W0970513004	M12X1 5-PIN 90° connector with wire L = 197 inch

## PRESSURE GAUGE




Code	Description
9700106	M 39 1/8 0-4 (0 to 60 psi)
9700107	M 39 1/8 0-12 (0 to 180 psi)

## THREADED PORT




Code	Description
9232001U	1/4" spare thr. port for ONE
9232002U	3/8" spare thr. port for ONE
9232003U	1/2" spare thr. port for ONE
9232004U	3/4" spare thr. port for ONE
9232005U	1" spare thr. port for ONE

## FILTER ELEMENT




Code	Description
9251720	Spare filter element 5 µm for ONE
9251721	Spare filter element 20 µm for ONE

## FILTER PLUG WITH FILTER ELEMENT



Code	Description
9251723	Spare plug + filter element 5 µm (790 microinch) for ONE
9251724	Spare plug + filter element 20 µm (2000 microinch) for ONE

## PILOT REGULATOR



Code	Description
9250820U	Spare pilot reg. 7 to 30 psi for ONE
9250821U	Spare pilot reg. 7 to 60 psi for ONE
9250822U	Spare pilot reg. 7 to 120 psi for ONE

## POPPET



Code	Description
9250707	Spare poppet for ONE

**SOLENOID VALVE**

NEW




Code	Description
722123840101	PLT-10 722123840101

OLD



**Note:** Spare part no longer available. If the solenoid valve to be replaced is the same as the one shown here on the left, please contact our sales department.


**PRESSURE SWITCH**



Code	Description
9000500	Spare press. switch for ONE

**Note:** with this kit we suggest you should order also the gauge, as it could get damaged during the disassembly.

**ELECTRIC BOARD**



Code	Description
9232010	Spare electric board for ONE

**Note:** with this kit we suggest you should order also the gauge, as it could get damaged during the disassembly.

**AUTOMATIC DRAIN (RA)**



Code	Description
9000802	Spare automatic drain (RA)

**NOTES**